

16 Core Fiber Optic Distribution Box

Description

This box is used as a termination point for the feeder cable to connect with drop cable in FTTH communication network system.

It integrates fiber splicing, splitting, distribution, storage and cable connection in one unit. Meanwhile, it provides solid protection and management for the FTTH network building.

Features

- 1. Total enclosed structure.
- 2. Material: ABS, wet-proof, water-proof, dust proof, anti-aging, protection level up to IP65.
- 3. Clamping for feeder cable and drop cable, fiber splicing, fixation, storage distribution ... etc all in one.
- 4. Cable, pigtails, patch cords are running through own path without disturbing each other, cassette type SC adaptor .installation, easy maintenance.
- 5. Distribution panel can be flipped up, feeder cable can be placed in a cup-joint way, easy for maintenance and installation.
- 6. Box can be installed by the way of wall-mounted or pole-mounted, suitable for both indoor and outdoor uses.



SC Type



PLC Type

: fej^l iXkf e

D Xk i Xc	J`q\	D Xo : XgXZ`kp	Nos of PLC	E f j f] 8[Xgkfi	N \^_k	Gf i kj
Strengthen Polymer Plastic	A*B*C(mm) 290*185*108	Splice 16 Fibers (1trays, 16 fiber/tray)	2 pcs of 1x8 1 pcs of 1x16	16 pcs of SC(max)	1.65kg	3 in 16 out

Applications

- Wall mounting and pole mounting installation
- FTTH pre-installation and field installation
- 4-7mm cable ports suitable for 2x3mm indoor FTTH drop cable and outdoor figure 8 FTTH self-supporting drop cable

Standard Accessories

Metal hanger : 2pcs

Cable tie:3mm*110mm 8pcs

Heat-shrink sleeve:1.2mm*60mm 16pcs

Hose clamps: 6pcs

Fiber protective tube: 1pcs

